

See Also

[GraffitiTabBarItem](#)

Enumerations

Name	Values
Positions	Top
	Bottom
	Left
	Right
Styles	Dark
	Light
	Rounded
	Gradient
	RoundedGradient

Constants

Name	Type	Value
Position		This class exposes no constants.

Events

Definition	Description
ConstructContextualMenu(theTab as GraffitiTabBarItem, byRef base as MenuItem, X as Integer, Y as Integer)	Fired when the ContextMenu needs to be created.
ContextualMenuAction(theTab as GraffitiTabBarItem, hitItem as MenuItem)	Fired when the user selects an item from the ContextMenu.
TabChange(theTab as GraffitiTabBarItem) as Boolean	Fired when the user clicks a tab, return false to negate change.
TabEnter(theTab as GraffitiTabBarItem)	Fired when the mouse enters a tab.
TabExit(theTab as GraffitiTabBarItem)	Fired when the mouse exits a tab.
TabRemove(theTab as GraffitiTabBarItem) as Boolean	Fired when the user attempts to remove a tab via the close button, return false to negate the removal.

Methods

Definition	Description
AddTab(theTab as GraffitiTabBarItem)	Adds a tab to the display.
GetIndex(theTab as GraffitiTabBarItem) as Integer	Returns the index of the supplied item.

Definition	Description
GetTab(theIndex as Integer) as GraffitiTabBarItem	Returns the item corresponding the supplied index.
GetTabByTag(theTag as Variant) as GraffitiTabBarItem	Returns the item whose tag is supplied by the theTag parameter.
GetTabByText(theText as String) as GraffitiTabBarItem	Returns the item whose text matches that supplied by the theText parameter.
InsertTab(theIndex as Integer, theTab as GraffitiTabBarItem)	Inserts the specified tab at the provided index.
RemoveAll()	Removes all tabs from the instance.
RemoveTab(theIndex as Integer)	Removes the tab at the specified index from the instance.
SelectTab(theIndex as Integer)	Selects the tab at the specified index.
SelectTab(theTab as GraffitiTabBarItem)	Selects the specified tab.

Properties

Name	Type	Default Value	Description
ActiveCloseColor	Color	&c000000	Color applied to the close icon of active tabs.
ActiveTabColor	Color	&c000000	Color applied to the background of active tabs.
ActiveTextColor	Color	&c000000	Color applied to the text of active tabs.
BackgroundColor	Color	&c000000	Color applied to the area of the bar not occupied by tabs.
ChevronColor	Color	&c000000	Color applied to the Chevron.
CustomColors	Boolean	False	If True, custom colors supplied via properties will be used rather than the defaults according to Style.
DownTextColor	Color	&c000000	Color applied to text on MouseDown on a tab.
DragReorder	Boolean	False	Allows the user to drag tags to change their order in the display.
HoverChevronColor	Color	&c000000	Color applied to the Chevron on hover.
HoverCloseColor	Color	&c000000	Color applied to tab close buttons on hover.
HoverTabColor	Color	&c000000	Color applied to tab backgrounds on hover.
HoverTextColor	Color	&c000000	Color applied to text on hover.
InactiveCloseColor	Color	&c000000	Color applied to close button when tab is unselected.
InactiveTabColor	Color	&c000000	Color applied to the tab background when tab is unselected.
InactiveTextColor	Color	&c000000	Color applied to tab text when tab is unselected.

From: Name	Type	Default Value	Description
https://graffitisuite.com/wiki/ - GraffitiSuite Documentation Permanent link: https://graffitisuite.com/wiki/doku.php?id=desktop:tabbar Last update: 2022/06/03 13:24	Integer	100	Maximum width of ellipsis to collapse width. Actual tab width. Actual tab close button width
MinimumTabWidth	Integer	10	Minimum width a tab can fill.
Position	GraffitiWebTabBar.Positions	Positions.Top	The direction the bar is to be displayed.
Style	GraffitiTabBar.Styles	Styles.Dark	The display style of the tabs.



Examples

There are currently no examples for this class.

Changes to this Page

Date	Edit	Editor
01/29/2018	Document Created	