

Enumerations

| Name | Values |
|------|-------------------------------------|
| | This class exposes no enumerations. |

Constants

| Name | Type | Value |
|------|------|----------------------------------|
| | | This class exposes no constants. |

Events

| Definition | Description |
|---------------|--|
| TextChanged() | This event is fired when the text of the field is changed (IE: when a date or range is selected in the popup). |

Methods

| Definition | Description |
|------------|---|
| | This class does not expose any methods. |

Properties

| Name | Type | Default Value | Description |
|------------------|---------|----------------|---|
| BracketNegatives | String | "" | Determines the display format of negative numbers: (###,###) [###,###] {###,###} <###,###> |
| CurrencySymbol | String | "" | The symbol displayed for the currency such as: \$ USD EUR |
| DecimalChar | String | “.” | The character used to denote the decimal position. |
| DecimalPlaces | Integer | 2 | Number of decimal places to display. |
| DisplayEmpty | String | “empty” | What to display when there is not numeric value in the field: empty, zero, sign |
| GroupCount | Integer | 3 | Amount of numbers in each group, separated by the ThousandsSep. |
| MaximumValue | Double | 9999999999.99 | The maximum possible value the field allows. |
| MinimumValue | Double | -9999999999.99 | The minimum possible value the field allows. |
| PadDecimal | Boolean | False | Determines whether the decimal places will always be shown regardless of whether there is any decimal value to display. |
| ReadOnly | Boolean | False | When True the user cannot edit the display, but the control appears enabled. |

| Name | Type | Default Value | Description |
|------------------|--------|---------------|---|
| RoundingStyle | String | "S" | S = Round Half Up Symmetrical A = Round Half Up Asymmetrical s = Round Half Down Symmetrical a = Round Half Down Asymmetrical B = Round Half Even U = Round Up D = Round Down C = Round to Ceiling F = Round to Floor |
| SymbolPlacement | String | "p" | Determines placement of the currency symbol: p = Prefix s = Suffix |
| Text Read - OnlY | String | "" | Returns the current formatted value in the display. |
| ThousandsSep | String | "," | The character used for separating groups of thousands. |
| Value | Double | 0 | The double value of the display. |

Examples

There are currently no examples for this class.

From:

<https://graffitisuite.com/wiki/> - **GraffitiSuite Documentation**

Permanent link:

<https://graffitisuite.com/wiki/doku.php?id=web:currencyfield>

Last update: **2018/08/02 19:58**

