

See Also

[GraffitiWebGrid](#)

Enumerations

| Name | Values |
|------|-------------------------------------|
| | This class exposes no enumerations. |

Constants

| Name | Type | Value |
|------|------|----------------------------------|
| | | This class exposes no constants. |

Events

| Definition | Description |
|------------|--|
| | This class does not expose any events. |

Methods

| Definition | Description |
|---|--|
| Constructor(rowCells as Dictionary, isEnabled as Boolean = True, rowTag as Variant = nil) | Creates an instance of this class with the parameters as property values. |
| Cell(Column as GraffitiWebGridColumn) as Variant | Returns the row's value for the defined column. |
| Cell(Column as GraffitiWebGridColumn, Assigns Value as Variant) | Sets row's value for the defined column. Should be used as myRow.Cell(myColumn) = newValue |

Properties

| Name | Type | Default Value | Description |
|--------------------|-----------------------------|------------------|--|
| Cells Read-Only | Dictionary | Empty Dictionary | The columns values contained within the row. This exposed to make enumeration for things like output more accessible. |
| Children Read-Only | Array of GraffitiWebGridRow | Empty Array | Contains the children of this row in the display. Children should be added and removed via the AddChild and RemoveChild methods of the Grid. |
| ColSpanField | GraffitiWebGridColumn | Nil | The column to apply the span to. Only one ColSpan per row is supported. |
| ColSpanLength | Integer | 1 | The number of columns to span with the value specified in ColSpanField. |
| Enabled | Boolean | True | Determines whether this row's cells will be editable when AutoEdit = True |
| Expanded | Boolean | False | Determines the expansion state of this child in Tree mode. |

| Name | Type | Default Value | Description |
|------------------|-------------------------|---------------|---|
| ID Read-Only | String | "" | This is automatically generated by the Grid and should never be altered. |
| Indent | Integer | 0 | This automatically generated by the Grid and should never be altered. |
| Parent Read-Only | GraffitiWebGridRow | Nil | The parent of this row. This is automatically generated by the Grid and should never be altered. |
| Selected | Boolean | False | True when the row is selected, False when not. Setting this value directly will update the Grid's selection. |
| Style | WebStyle | Nil | Style applied to cells in this row. Overrides everything except for style specified by AddCellStyle. |
| Tag | Variant | Nil | Use for storing things like your database field key. This value has no functional application beyond being used for your reference. |

Examples

There are currently no examples for this class.

From: <https://graffitisuite.com/wiki/> - **GraffitiSuite Documentation**

Permanent link: <https://graffitisuite.com/wiki/doku.php?id=web:grid2row&rev=1530943165>

Last update: **2018/07/07 05:59**

